

# Package ‘danstat’

July 22, 2025

**Type** Package

**Title** R Client for the Statistics Denmark Databank API

**Version** 0.2.0

**Author** Valeri Voev

**Maintainer** Valeri Voev <v\_voev@yahoo.com>

**Description** The purpose of the package is to enable an R function interface into the Statistics Denmark Databank API mainly for research purposes.

The Statistics Denmark Databank API has four endpoints, see here for more information and testing the API in their console: <<https://www.dst.dk/en/Statistik/brug-statistikken/muligheder-i-statistikbanken/api>>.

This package mimics the structure of the API and provides four main functions to match the functionality of the API endpoints.

**License** MIT + file LICENSE

**Encoding** UTF-8

**RoxygenNote** 7.1.2

**Imports** httr, jsonlite, readr

**Suggests** testthat (>= 2.1.0), knitr, rmarkdown, purrr, dplyr, ggplot2, kableExtra

**VignetteBuilder** knitr

**NeedsCompilation** no

**Repository** CRAN

**Date/Publication** 2022-01-31 08:10:02 UTC

## Contents

get_data . . . . .	2
get_subjects . . . . .	3
get_tables . . . . .	4
get_table_metadata . . . . .	5

<b>Index</b>	<b>6</b>
--------------	----------

---

get_data	<i>Get data for a particular table and variable selection</i>
----------	---

---

## Description

Get data for a particular table and variable selection

## Usage

```
get_data(table_id, variables, language = c("en", "da"))
```

## Arguments

table_id	Table identifier, e.g. "folk1a"
variables	A list with variable code-values pairs. Each code-values pair should be a named list with names "code" and "values". If all values for a variable are desired, define values = NA for that variable code.
language	Language for the return object. Default = "en"

## Value

A data frame

## Examples

```
# Get data from table "folk1c" for selected values of variables "ieland" and "køn"
# and all time periods available.

# The "ieland" variable is filtered for Denmark (id = 5000) and Bulgaria (id = 5128)
# and the "køn" variable id filtered for Men (id = 1) and Women (id = 2).
# The "tid" variable is unfiltered, i.e. selects all available time periods
# See get_table_metadata(table_id = "folk1c", variables_only = TRUE) for variable codes and values.

variables <- list(list(code = "ieland", values = c(5100, 5128)),
                 list(code = "køn", values = c(1,2)),
                 list(code = "tid", values = NA))

data <- get_data("folk1c", variables)
```

---

get_subjects	<i>Get a list of subjects covered in the data bank</i>
--------------	--

---

### Description

Get a list of subjects covered in the data bank

### Usage

```
get_subjects(  
  subjects = NULL,  
  recursive = FALSE,  
  include_tables = FALSE,  
  language = c("en", "da")  
)
```

### Arguments

subjects	Provide specific subject id's to get subtopics. E.g. subjects = c("02", "2419")
recursive	Whether subtopics/tables will be retrieved all the way down the hierarchy. Otherwise, only the closest level under the provided subjects will be retrieved. Default = FALSE
include_tables	Whether the result should contain tables. Otherwise, only subjects are returned. Default = FALSE
language	Language for the return object. Default = "en"

### Value

A data frame

### Examples

```
# Get all subjects  
all_subjects <- get_subjects()  
  
# Or get (sub)subjects for specific subjects  
some_subjects <- get_subjects(subjects = c("2", "3"))  
  
# Get all subject hierarchy for a given subject  
subject_with_hierarchy <- get_subjects(subjects = "2", recursive = TRUE)
```

---

get_tables	<i>Get a list of stables in the data bank</i>
------------	---

---

### Description

Get a list of stables in the data bank

### Usage

```
get_tables(  
  subjects = NULL,  
  pastdays = NA_integer_,  
  include_inactive = FALSE,  
  language = c("en", "da")  
)
```

### Arguments

subjects	Provide specific subject id's to get subtopics. E.g. subjects = c("02", "2419"). Can be retrieved with get_subjects()
pastdays	Return only tables which have been updated within this number of days
include_inactive	Whether to return tables that are no longer updated
language	Language for the return object. Default = "en"

### Value

A data frame

### Examples

```
# Get all tables  
all_tables <- get_tables()  
  
# Or get tables for specific subjects  
some_tables <- get_tables(subjects = c("2", "3413"))  
  
# Get all tables updated within the past 3 days  
tables_past3days <- get_tables(pastdays = 3)
```

---

get_table_metadata	<i>Title</i>
--------------------	--------------

---

**Description**

Title

**Usage**

```
get_table_metadata(table_id, variables_only = FALSE, language = c("en", "da"))
```

**Arguments**

table\_id            Table identifier, e.g. "folk1a"  
variables\_only    If TRUE returns only information about the variables in the table  
language            Language for the return object. Default = "en"

**Value**

A list with information about the table, like documentation url, variable description, etc. If variables\_only = TRUE, returns a data frame with variable information.

**Examples**

```
# Get table metadata for a given table  
table_meta <- get_table_metadata(table_id = "folk1c") # a list  
  
# Get only information about the variables in the table  
table_meta_vars <- get_table_metadata(table_id = "folk1c", variables_only = TRUE) # a data frame
```

# Index

`get_data`, [2](#)  
`get_subjects`, [3](#)  
`get_table_metadata`, [5](#)  
`get_tables`, [4](#)