

Package ‘epigraphdb’

October 13, 2022

Title Interface Package for the 'EpiGraphDB' Platform

Version 0.2.3

Description The interface package to access data from the 'EpiGraphDB' <<https://epigraphdb.org>> platform.

It provides easy access to the 'EpiGraphDB' platform with functions that query the corresponding REST endpoints on the API <<https://api.epigraphdb.org>> and return the response data in the 'tibble' data frame format.

URL <https://mrcieu.github.io/epigraphdb-r/>

BugReports <https://github.com/MRCIEU/epigraphdb-r/issues>

License GPL-3

Suggests testthat, roxygen2, knitr, rmarkdown, spelling, devtools, usethis, pkgdown, styler, lintr, covr, igraph, gtools, stringr, dplyr, ggplot2

Encoding UTF-8

RoxygenNote 7.1.2

Imports magrittr, tibble, httr, glue, purrr, jsonlite

VignetteBuilder knitr

Language en-GB

NeedsCompilation no

Author Yi Liu [cre, aut],
Valeria Haberland [aut],
Marina Vabistsevits [aut],
Tom Gaunt [aut],
MRC IEU [cph]

Maintainer Yi Liu <yi6240.liu@bristol.ac.uk>

Repository CRAN

Date/Publication 2022-01-14 19:52:45 UTC

R topics documented:

confounder	2
cypher	3
drugs_risk_factors	4
genetic_cor	5
literature_gwas	6
mappings_gene_to_protein	6
meta_nodes_list	7
meta_nodes_list_node	8
meta_nodes_search_node	9
meta_rels_list	10
meta_rels_list_rel	11
mr	11
obs_cor	13
ontology_gwas_efo	14
pathway	15
pqt1	15
pqt1_list	17
pqt1_pleio	18
protein_in_pathway	19
query_epigraphdb	19
xqtl_multi.snp_mr	21
xqtl_single.snp_mr	22

Index	24
-------	----

confounder	<i>MR evidence on confounding traits between exposure and outcome</i>
------------	---

Description

GET /confounder

Usage

```
confounder(
  exposure_trait = NULL,
  outcome_trait = NULL,
  type = c("confounder", "intermediate", "reverse_intermediate", "collider"),
  pval_threshold = 1e-05,
  mode = c("table", "raw")
)
```

Arguments

exposure_trait	A trait name, e.g. "Body mass index", leaving exposure_trait as NULL will return MR information related to a specific outcome. NOTE: exposure_trait and outcome_trait cannot be both NULL.
outcome_trait	A trait name, e.g. "Coronary heart disease", leaving outcome_trait as NULL will return MR information related to a specific exposure_trait. NOTE: exposure_trait and outcome_trait cannot be both NULL.
type	One in ["confounder", "intermediate", "reverse_intermediate", "collider"] Refer to the confounder view in web application for details
pval_threshold	P-value threshold
mode	If mode = "table", returns a data frame (a tibble as per tidyverse convention). If mode = "raw", returns a raw response from EpiGraphDB API with minimal parsing done by httr .

Value

Data from GET /confounder

Examples

```
## Not run:  
confounder(exposure_trait = "Body mass index", outcome_trait = "Coronary heart disease")  
  
## End(Not run)
```

cypher

Send a query in Cypher to EpiGraphDB

Description

NOTE: this function is intended for advanced uses. Regular users are recommended to use standard query functions

Usage

```
cypher(query, mode = c("table", "raw"))
```

Arguments

query	A Cypher query.
mode	If mode = "table", returns a data frame (a tibble as per tidyverse convention). If mode = "raw", returns a raw response from EpiGraphDB API with minimal parsing done by httr .

Examples

```
## Not run:
cypher("MATCH (n:Gwas) RETURN n LIMIT 2")

## End(Not run)
```

drugs_risk_factors *Drugs for risk factors*

Description

GET /drugs/risk-factors

Usage

```
drugs_risk_factors(trait, pval_threshold = 1e-08, mode = c("table", "raw"))
```

Arguments

trait	A trait name
pval_threshold	P-value threshold
mode	If mode = "table", returns a data frame (a tibble as per tidyverse convention). If mode = "raw", returns a raw response from EpiGraphDB API with minimal parsing done by httr .

Value

Data from GET /drugs/risk-factors

Examples

```
## Not run:
drugs_risk_factors(trait = "Body mass index")

## End(Not run)
```

genetic_cor	<i>Genetic correlations between traits</i>
-------------	--

Description

`GET /genetic-cor`

Usage

```
genetic_cor(trait, cor_coef_threshold = 0.8, mode = c("table", "raw"))
```

Arguments

trait	name of the trait, e.g. "body mass index"
cor_coef_threshold	correlation coefficient threshold
mode	If mode = "table", returns a data frame (a <code>tibble</code> as per <code>tidyverse</code> convention). If mode = "raw", returns a raw response from EpiGraphDB API with minimal parsing done by <code>httr</code> .

Value

Data from GET /genetic_cor

Examples

```
## Not run:  
genetic_cor(trait = "Body mass index") %>%  
  dplyr::glimpse()  
  
## End(Not run)  
  
# Use a different threshold  
## Not run:  
genetic_cor(trait = "Body mass index", cor_coef_threshold = 0.4) %>%  
  dplyr::glimpse()  
  
## End(Not run)
```

`literature_gwas` *Literature evidence regarding a GWAS trait*

Description

GET /literature/gwas

Usage

```
literature_gwas(trait, semmed_predicate = NULL, mode = c("table", "raw"))
```

Arguments

<code>trait</code>	A trait name
<code>semmed_predicate</code>	Either NULL which returns entries from all predicates, or a SemMed predicate e.g. "DIAGNOSES" or "ASSOCIATED_WITH"
<code>mode</code>	If mode = "table", returns a data frame (a <code>tibble</code> as per <code>tidyverse</code> convention). If mode = "raw", returns a raw response from EpiGraphDB API with minimal parsing done by <code>httr</code> .

Value

Data from GET /literature/gwas

Examples

```
## Not run:
literature_gwas(trait = "Body mass index")

## End(Not run)
```

`mappings_gene_to_protein` *Return protein uniprot_id from associated genes*

Description

POST /mappings/gene-to-protein

Usage

```
mappings_gene_to_protein(
  gene_name_list = NULL,
  gene_id_list = NULL,
  by_gene_id = FALSE,
  mode = c("table", "raw")
)
```

Arguments

- `gene_name_list` List of HGNC symbols of the genes (default)
- `gene_id_list` List of Ensembl gene IDs (when `by_gene_id == TRUE`)
- `by_gene_id` Search for gene ids (Ensembl gene IDs) instead of gene names (HGNC symbols)
- `mode` If `mode = "table"`, returns a data frame (a `tibble` as per `tidyverse` convention). If `mode = "raw"`, returns a raw response from EpiGraphDB API with minimal parsing done by `httr`.

Value

Data from POST /mappings/gene-to-protein

Examples

```
# By HGNC symbols
## Not run:
mappings_gene_to_protein(gene_name_list = c("GCH1", "MYOF"))

## End(Not run)

# By Ensembl Ids
## Not run:
mappings_gene_to_protein(gene_id_list = c("ENSG00000162594", "ENSG00000113302"), by_gene_id = TRUE)

## End(Not run)
```

`meta_nodes_list` *List meta nodes (e.g. Gwas, Gene, etc.)*

Description

GET /meta/nodes/list

Usage

```
meta_nodes_list(mode = c("raw"))
```

Arguments

- `mode` If `mode = "table"`, returns a data frame (a `tibble` as per `tidyverse` convention). If `mode = "raw"`, returns a raw response from EpiGraphDB API with minimal parsing done by `httr`.

Value

Data from GET /meta/nodes/list

Examples

```
## Not run:
meta_nodes_list()

## End(Not run)
```

meta_nodes_list_node *List nodes under a meta node*

Description

GET /meta/nodes/{meta_node}/list

Usage

```
meta_nodes_list_node(
  meta_node,
  full_data = TRUE,
  limit = 10,
  offset = 0,
  mode = c("table", "raw")
)
```

Arguments

<code>meta_node</code>	Name of a meta node (e.g. Gwas). Use <code>meta_nodes_list</code> to get the full list of meta nodes.
<code>full_data</code>	When <code>False</code> , only return the <code>id</code> and <code>name</code> fields (their specific names differ in specific nodes) for a node. This is useful if you want your queries to return results faster with smaller amount of data requested.
<code>limit</code>	Max number of items to retrieve.
<code>offset</code>	Number of items to skip. Use <code>limit</code> and <code>offset</code> in combination to do pagination.
<code>mode</code>	If <code>mode = "table"</code> , returns a data frame (a <code>tibble</code> as per <code>tidyverse</code> convention). If <code>mode = "raw"</code> , returns a raw response from EpiGraphDB API with minimal parsing done by <code>httr</code> .

Value

Data from GET /meta/nodes/{meta_node}/list

Examples

```
# List the first 5 Gwas nodes, with only id and name fields
## Not run:
meta_nodes_list_node(meta_node = "Gwas", full_data = FALSE, limit = 5)

## End(Not run)

# List the 6th - 10th Disease nodes, with full properties
## Not run:
meta_nodes_list_node(meta_node = "Disease", full_data = TRUE, limit = 5, offset = 0)

## End(Not run)
```

meta_nodes_search_node

Search a node by its id field, or its name field

Description

GET /meta/nodes/{meta_node}/search

Usage

```
meta_nodes_search_node(
  meta_node,
  id = NULL,
  name = NULL,
  limit = 10,
  full_data = TRUE,
  mode = c("table", "raw")
)
```

Arguments

meta_node	Name of a meta node (e.g. Gwas). Use <code>meta_nodes_list</code> to get the full list of meta nodes.
id	The id field of a node (e.g. "ieu-a-2" for a Gwas). Use EpiGraphDB web UI to get a sense of what those ids are for entities.
name	The name field of a node (e.g. "body mass index" for a Gwas). Use EpiGraphDB web UI to get a sense of what those names are for entities.
limit	Max number of items to retrieve.
full_data	When False, only return the id and name fields (their specific names differ in specific nodes) for a node. This is useful if you want your queries to return results faster with smaller amount of data requested.
mode	If <code>mode = "table"</code> , returns a data frame (a <code>tibble</code> as per <code>tidyverse</code> convention). If <code>mode = "raw"</code> , returns a raw response from EpiGraphDB API with minimal parsing done by <code>httr</code> .

Value

Data from GET /meta/nodes/{meta_node}/search

Examples

```
# Search Gwas nodes
## Not run:
meta_nodes_search_node(meta_node = "Gwas", name = "body mass index")

## End(Not run)
```

meta_rels_list *List meta rels (e.g. MR, etc.)*

Description

GET /meta/rels/list

Usage

```
meta_rels_list(mode = c("raw"))
```

Arguments

mode	If mode = "table", returns a data frame (a tibble as per tidyverse convention). If mode = "raw", returns a raw response from EpiGraphDB API with minimal parsing done by httr .
------	--

Value

Data from GET /meta/rels/list

Examples

```
## Not run:
meta_rels_list()

## End(Not run)
```

<code>meta_rels_list_rel</code>	<i>List relationships under a meta relationship</i>
---------------------------------	---

Description

`GET /meta/rels/{meta_rel}/list`

Usage

```
meta_rels_list_rel(meta_rel, limit = 10, offset = 0, mode = c("table", "raw"))
```

Arguments

<code>meta_rel</code>	Name of a meta relationship (e.g. MR). Use <code>meta_rels_list</code> to get the full list of meta relationships.
<code>limit</code>	Max number of items to retrieve.
<code>offset</code>	Number of items to skip. Use <code>limit</code> and <code>offset</code> in combination to do pagination.
<code>mode</code>	If <code>mode = "table"</code> , returns a data frame (a <code>tibble</code> as per <code>tidyverse</code> convention). If <code>mode = "raw"</code> , returns a raw response from EpiGraphDB API with minimal parsing done by <code>httr</code> .

Value

Data from `GET /meta/rels/{meta_rel}/list`

Examples

```
# List the first 5 MR relationships
## Not run:
meta_rels_list_rel(meta_rel = "MR_EVE_MR", limit = 5)

## End(Not run)
```

<code>mr</code>	<i>Return information related to Mendelian Randomisation</i>
-----------------	--

Description

`GET /mr`

Usage

```
mr(
  exposure_trait = NULL,
  outcome_trait = NULL,
  pval_threshold = 1e-05,
  mode = c("table", "raw")
)
```

Arguments

- `exposure_trait` A trait name, e.g. "Body mass index", leaving `exposure_trait` as `NULL` will return MR information related to a specific `outcome`. **NOTE:** `exposure_trait` and `outcome_trait` cannot be both `NULL`.
- `outcome_trait` A trait name, e.g. "Coronary heart disease", leaving `outcome_trait` as `NULL` will return MR information related to a specific `exposure_trait`. **NOTE:** `exposure_trait` and `outcome_trait` cannot be both `NULL`.
- `pval_threshold` P-value threshold
- `mode` If `mode = "table"`, returns a data frame (a `tibble` as per `tidyverse` convention). If `mode = "raw"`, returns a raw response from EpiGraphDB API with minimal parsing done by `httr`.

Value

Data from GET /`mr`

Examples

```
# Returns a data frame
## Not run:
mr(exposure_trait = "Body mass index", outcome_trait = "Coronary heart disease")

## End(Not run)

# Returns raw response
## Not run:
mr(
  exposure_trait = "Body mass index", outcome_trait = "Coronary heart disease",
  mode = "raw"
) %>% str()

## End(Not run)

# Use a different threshold
## Not run:
mr(exposure_trait = "Body mass index", pval_threshold = 1e-8)

## End(Not run)
```

obs_cor

Observational correlations between traits

Description

`GET /obs-cor`

Usage

```
obs_cor(trait, cor_coef_threshold = 0.8, mode = c("table", "raw"))
```

Arguments

trait	name of the trait, e.g. "body mass index"
cor_coef_threshold	correlation coefficient threshold
mode	If mode = "table", returns a data frame (a <code>tibble</code> as per <code>tidyverse</code> convention). If mode = "raw", returns a raw response from EpiGraphDB API with minimal parsing done by <code>httr</code> .

Value

Data from GET /obs-cor

Examples

```
## Not run:  
obs_cor(trait = "Body mass index (BMI)") %>%  
  dplyr::glimpse()  
  
## End(Not run)  
  
# Use a different threshold  
## Not run:  
obs_cor(trait = "Body mass index (BMI)", cor_coef_threshold = 0.8) %>%  
  dplyr::glimpse()  
  
## End(Not run)
```

ontology_gwas_efo*Ontology association between EFO term and Gwas***Description**

`GET /ontology/gwas-efo`

Usage

```
ontology_gwas_efo(
  trait = NULL,
  efo_term = NULL,
  fuzzy = TRUE,
  mode = c("table", "raw")
)
```

Arguments

<code>trait</code>	trait name, e.g. "body mass"
<code>efo_term</code>	EFO term, e.g. "systolic blood pressure"
<code>fuzzy</code>	whether query with exact matching (FALSE) or fuzzy matching (default, TRUE)
<code>mode</code>	If <code>mode = "table"</code> , returns a data frame (a <code>tibble</code> as per <code>tidyverse</code> convention). If <code>mode = "raw"</code> , returns a raw response from EpiGraphDB API with minimal parsing done by <code>httr</code> .

Value

Data from `GET /ontology/gwas-efo`

Examples

```
## Not run:
ontology_gwas_efo(trait = "blood", fuzzy = FALSE)

## End(Not run)

## Not run:
ontology_gwas_efo(efo_term = "blood pressure", fuzzy = FALSE)

## End(Not run)
```

pathway	<i>Pathway evidence</i>
---------	-------------------------

Description**GET /pathway****Usage**

```
pathway(trait, pval_threshold = 1e-05, mode = c("table", "raw"))
```

Arguments

trait	A trait name
pval_threshold	P-value threshold
mode	If mode = "table", returns a data frame (a tibble as per tidyverse convention). If mode = "raw", returns a raw response from EpiGraphDB API with minimal parsing done by httr .

Value

Data from GET /pathway

Examples

```
## Not run:
pathway(trait = "Body mass index")

## End(Not run)
```

pqt1	<i>Return information related to the pQTL analysis</i>
------	--

Description**GET /pqt1/****Usage**

```
pqt1(
  query,
  rtype = c("mrres", "simple", "sglmr", "inst", "sense"),
  pvalue = 0.05,
  searchflag = c("traits", "proteins"),
  mode = c("table", "raw")
)
```

Arguments

query	(Required) A protein coding gene name or a trait name, e.g. "ADAM19" or "Inflammatory bowel disease" which cannot be NULL.
rtype	(Optional) A type of data to be extracted, which can be one of these options: 1. simple: Basic summary 2. mrres: MR results (DEFAULT) 3. sglmr: Single SNP MR results 4. inst: SNP information 5. sense: Sensitivity analysis NOTE: mrres is a DEFAULT option.
pvalue	(Optional) A pvalue threshold for MR results with the DEFAULT set to 0.05. NOTE: this threshold applies to any rtype chosen.
searchflag	(Required) A flag to indicate whether you are searching for proteins or traits which cannot be NULL. If query is a protein name, then this flag should be "proteins"; if query is a trait, this flag should be "traits". NOTE: if the wrong flag is chosen for query, there will be no result returned.
mode	If mode = "table", returns a data frame (a tibble as per tidyverse convention). If mode = "raw", returns a raw response from EpiGraphDB API with minimal parsing done by httr .

Value

Data from GET /pql/

Examples

```
# Returns a data frame of MR results, while searching for proteins
## Not run:
pql(query = "ADAM19", searchflag = "proteins")

## End(Not run)

# Returns a data frame with SNP information, while searching for traits
## Not run:
pql(
  query = "Inflammatory bowel disease",
  rtype = "inst",
  searchflag = "traits"
)

## End(Not run)

# Change a pvalue threshold (the default is 0.05)
## Not run:
pql(
  query = "Inflammatory bowel disease",
  rtype = "inst",
  pvalue = 1.0,
  searchflag = "traits"
```

```

)
## End(Not run)

# Returns raw response if mode="raw"
## Not run:
pqtl(
  query = "ADAM19", searchflag = "proteins",
  mode = "raw"
) %>% str()

## End(Not run)

```

pqtl_list

Return a list of all proteins/exposures or traits/outcomes available in the database

Description

`GET /pqtl/list/`

Usage

```
pqtl_list(flag = c("exposures", "outcomes"), mode = c("table", "raw"))
```

Arguments

flag	(Optional) A flag which indicates whether the list of exposures (if "exposures") or outcomes (if "outcomes") should be returned. The DEFAULT is "exposures".
mode	If mode = "table", returns a data frame (a <code>tibble</code> as per <code>tidyverse</code> convention). If mode = "raw", returns a raw response from EpiGraphDB API with minimal parsing done by <code>httr</code> .

Value

Data from `GET /pqtl/list/`

Examples

```

# Returns a list of available proteins (exposures)
## Not run:
pqtl_list()

## End(Not run)

# Returns a list of available traits (outcomes)
## Not run:
pqtl_list(flag = "outcomes")

## End(Not run)

```

pqtl_pleio*Return information related to the pleiotropy of SNPs***Description**`GET /pqtl/pleio/`**Usage**

```
pqtl_pleio(
  rsid = NULL,
  prflag = c("proteins", "count"),
  mode = c("table", "raw")
)
```

Arguments

<code>rsid</code>	(Required) A SNP identified by rsID which cannot be NULL.
<code>prflag</code>	(Optional) A flag which determines whether the number (if "count") or names (if "proteins") of the associated proteins should be returned. The DEFAULT value is "proteins".
<code>mode</code>	(Optional) If <code>mode = "table"</code> , returns a data frame (a <code>tibble</code> as per <code>tidyverse</code> convention). If <code>mode = "raw"</code> , returns a raw response from EpiGraphDB API with minimal parsing done by <code>httr</code> .

ValueData from `GET /pqtl/pleio/`**Examples**

```
# Returns a data frame of associated proteins
## Not run:
pqtl_pleio(rsid = "rs1260326")

## End(Not run)

# Returns a number of associated proteins
## Not run:
pqtl_pleio(rsid = "rs1260326", prflag = "count")

## End(Not run)
```

protein_in_pathway *For the list of proteins, returns their associated pathway data*

Description

`POST /protein/in-pathway`

Usage

```
protein_in_pathway(uniprot_id_list, mode = c("table", "raw"))
```

Arguments

uniprot_id_list	A list of protein UniProt IDs
mode	If <code>mode = "table"</code> , returns a data frame (a <code>tibble</code> as per <code>tidyverse</code> convention). If <code>mode = "raw"</code> , returns a raw response from EpiGraphDB API with minimal parsing done by <code>httr</code> .

Value

Data from `POST /protein/in-pathway`

Examples

```
## Not run:  
protein_in_pathway(uniprot_id_list = c("014933", "060674", "P32455"))  
  
## End(Not run)
```

query_epigraphdb *Send data request to an EpiGraphDB API endpoint*

Description

This is a general purpose function to send data request which can be used when there has not been an R equivalent package function to an API endpoint. Underneath this is a wrapper around `httr` functions with better handling of returned status.

Usage

```
query_epigraphdb(
  route,
  params = NULL,
  mode = c("raw", "table"),
  method = c("GET", "POST"),
  retry_times = 3,
  retry_pause_min = 1
)
```

Arguments

<code>route</code>	An EpiGraphDB API endpoint route, e.g. <code>"/mr"</code> or <code>"/confounder"</code> . Consult the EpiGraphDB API documentation .
<code>params</code>	A list of parameters associated with the query endpoint.
<code>mode</code>	<code>c("raw", "table")</code> , if <code>"table"</code> then the query handler will try to convert the returned data to a tibble dataframe. NOTE: The default mode is <code>"raw"</code> which will NOT convert the returned response to a dataframe. This is different to functions that query topic endpoints which default to return a dataframe. Explicitly specify <code>mode = "table"</code> when needed.
<code>method</code>	Type of HTTP (GET, POST, PUT, etc.) method. NOTE: When sending a POST request where a specific parameter is specified as a list on the API, and if the equivalent in R is a vector of length 1, you should wrap this parameter in <code>I()</code> , e.g. <code>I(c("APOE"))</code> to avoid auto unboxing. For details, please refer to httr::POST
<code>retry_times</code>	Number of times the function will retry the request to the API.
<code>retry_pause_min</code>	Minimum number of seconds to wait for the next retry.

Value

Data from an EpiGraphDB API endpoint.

Examples

```
# GET /mr
# equivalent to `mr(exposure_trait = "Body mass index", outcome_trait = "Coronary heart disease")` 
## Not run:
query_epigraphdb(
  route = "/mr",
  params = list(
    exposure_trait = "Body mass index",
    outcome_trait = "Coronary heart disease"
  ),
  mode = "table"
)

## End(Not run)
```

```

# GET /meta/nodes/Gwas/list
## Not run:
query_epigraphdb(
  route = "/meta/nodes/Gwas/list",
  params = list(
    limit = 5,
    offset = 0
  )
) %>% str(1)

## End(Not run)

# POST /protein/ppi
## Not run:
query_epigraphdb(
  route = "/protein/ppi",
  params = list(
    uniprot_id_list = c("P30793", "Q9NZM1", "095236")
  ),
  method = "POST"
)
## End(Not run)

# error handling
## Not run:
tryCatch(
  query_epigraphdb(
    route = "/mr",
    params = list(
      exposure_trait = NULL,
      outcome_trait = NULL
    ),
    retry_times = 0
  ),
  error = function(e) {
    message(e)
  }
)
## End(Not run)

```

xqtl_multi.snp_mr *Multi SNP QTL MR evidence*

Description

GET /xqtl/multi-snp-mr

Usage

```
xqtl_multi.snp_mr(
  exposure_gene = NULL,
  outcome_trait = NULL,
  mr_method = c("IVW", "Egger"),
  qtl_type = c("eQTL", "pQTL"),
  pval_threshold = 1e-05,
  mode = c("table", "raw")
)
```

Arguments

exposure_gene	Name of the exposure gene
outcome_trait	Name of the outcome trait
mr_method	"IVW" or "Egger"
qtl_type	"eQTL" or "pQTL"
pval_threshold	P-value threshold
mode	If mode = "table", returns a data frame (a tibble as per tidyverse convention). If mode = "raw", returns a raw response from EpiGraphDB API with minimal parsing done by httr .

Value

Data from GET /xqtl/multi-snp-mr

Examples

```
## Not run:
xqtl_multi.snp_mr(outcome_trait = "Coronary heart disease")

## End(Not run)
```

xqtl_single.snp_mr *Single SNP QTL MR evidence*

Description

GET /xqtl/single-snp-mr

Usage

```
xqtl_single.snp_mr(
  exposure_gene = NULL,
  outcome_trait = NULL,
  snp = NULL,
  qtl_type = c("eQTL", "pQTL"),
```

```
    pval_threshold = 1e-05,  
    mode = c("table", "raw")  
)
```

Arguments

exposure_gene Name of the exposure gene
outcome_trait Name of the outcome trait
snp SNP rsid
qtl_type "eQTL" or "pQTL"
pval_threshold P-value threshold
mode If mode = "table", returns a data frame (a **tibble** as per **tidyverse** convention). If mode = "raw", returns a raw response from EpiGraphDB API with minimal parsing done by **httr**.

Value

Data from GEET /xqtl/single-snp-mr

Examples

```
## Not run:  
xqtl_single.snp_mr(outcome_trait = "Coronary heart disease")  
  
## End(Not run)
```

Index

confounder, 2
cypher, 3

drugs_risk_factors, 4

genetic_cor, 5

literature_gwas, 6

mappings_gene_to_protein, 6
meta_nodes_list, 7
meta_nodes_list_node, 8
meta_nodes_search_node, 9
meta_rels_list, 10
meta_rels_list_rel, 11
mr, 11

obs_cor, 13
ontology_gwas_efo, 14

pathway, 15
pqtl, 15
pqtl_list, 17
pqtl_pleio, 18
protein_in_pathway, 19

query_epigraphdb, 19

xqtl_multi.snp_mr, 21
xqtl_single.snp_mr, 22