

Package ‘rd2d’

October 24, 2025

Type Package

Title Boundary Regression Discontinuity Designs

Version 0.0.3

URL <https://rdpackages.github.io/rd2d/>

Description

Provides estimation and inference procedures for boundary regression discontinuity (RD) designs using local polynomial methods, based on either bivariate coordinates or distance-based approaches.

Methods are developed in Cattaneo, Titiunik, and Yu (2025)

<[https:](https://mdcattaneo.github.io/papers/Cattaneo-Titiunik-Yu_2025_BoundaryRD.pdf)

[//mdcattaneo.github.io/papers/Cattaneo-Titiunik-Yu_2025_BoundaryRD.pdf](https://mdcattaneo.github.io/papers/Cattaneo-Titiunik-Yu_2025_BoundaryRD.pdf)>.

Imports MASS, expm, ggplot2, stringr

License GPL-2

Encoding UTF-8

RoxygenNote 7.3.2

Maintainer Ruiqi Rae Yu <rae.yu@princeton.edu>

NeedsCompilation no

Author Matias D. Cattaneo [aut],
Rocio Titiunik [aut],
Ruiqi Rae Yu [aut, cre]

Repository CRAN

Date/Publication 2025-10-24 20:20:02 UTC

Contents

rd2d-package	2
print.rd2d	3
print.rd2d.dist	4
print.rdbw2d	4
print.rdbw2d.dist	5
rd2d	6

rd2d.dist	10
rdbw2d	14
rdbw2d.dist	18
summary.rd2d	21
summary.rd2d.dist	22
summary.rdbw2d	23
summary.rdbw2d.dist	24
Index	26

rd2d-package	<i>rd2d: Two Dimensional Local Polynomial Regression Discontinuity Design</i>
--------------	---

Description

This package implements estimation and inference procedures for boundary regression discontinuity (RD) designs using local polynomial methods, based on either bivariate coordinates or distance-based approaches. Methods are developed in Cattaneo, Titiunik, and Yu (2025a). A companion software article is available at Cattaneo, Titiunik, and Yu (2025b).

Included functions are: `rd2d` for inference and estimation based on bivariate coordinates, `rdbw2d` for data-driven bandwidth selection based on bivariate coordinates, `rd2d.dist` for distance-based inference and estimation, `rdbw2d.dist` for distance-based bandwidth selection.

`print()` and `summary()` methods are available all four functions.

Related Stata, R, and Python packages useful for inference in RD designs are described in the following website:

<https://rdpackages.github.io/>

For an introduction to regression discontinuity design, see Cattaneo, Idrobo, Titiunik (2024) and references therein.

Author(s)

Matias Cattaneo, Princeton University. <cattaneo@princeton.edu>. Rocio Titiunik, Princeton University. <titiunik@princeton.edu>. Ruiqi Rae Yu, Princeton University. <rae.yu@princeton.edu>.

References

- Cattaneo, M. D., Titiunik, R., Yu, R. R. (2025a). Estimation and Inference in Boundary Discontinuity Designs
- Cattaneo, M. D., Titiunik, R., Yu, R. R. (2025b). rd2d: Causal Inference in Boundary Discontinuity Designs
- Cattaneo, M. D., Idrobo, N., Titiunik, R. (2024). A Practical Introduction to Regression Discontinuity Designs: Extensions

See Also

Useful links:

- <https://rdpackages.github.io/rd2d/>

print.rd2d

Print Method for 2D Local Polynomial RD Estimation

Description

Prints the results of a 2D local polynomial regression discontinuity (RD) estimation, as obtained from [rd2d](#).

Usage

```
## S3 method for class 'rd2d'  
print(x, ...)
```

Arguments

x	An object of class rd2d, returned by rd2d .
...	Additional arguments passed to the method (currently ignored).

Value

No return value. This function is called for its side effects, which are to print the [rd2d](#) results.

Author(s)

Matias D. Cattaneo, Princeton University. <cattaneo@princeton.edu>
Rocío Titiunik, Princeton University. <titiunik@princeton.edu>
Ruiqi Rae Yu, Princeton University. <rae.yu@princeton.edu>

See Also

[rd2d](#) for conducting 2D local polynomial RD estimation.

Supported methods: [print.rd2d](#), [summary.rd2d](#).

print.rd2d.dist	<i>Print Method for 2D Local Polynomial RD Estimation (Distance-Based)</i>
-----------------	--

Description

Prints the results of a 2D local polynomial regression discontinuity (RD) estimation using distance-based evaluation, as obtained from [rd2d.dist](#).

Usage

```
## S3 method for class 'rd2d.dist'
print(x, ...)
```

Arguments

x	An object of class <code>rd2d.dist</code> , returned by rd2d.dist .
...	Additional arguments passed to the method (currently ignored).

Value

No return value. This function is called for its side effects: it prints the [rd2d.dist](#) results.

Author(s)

Matias D. Cattaneo, Princeton University. <cattaneo@princeton.edu>
 Rocío Titiunik, Princeton University. <titiunik@princeton.edu>
 Ruiqi Rae Yu, Princeton University. <rae.yu@princeton.edu>

See Also

[rd2d.dist](#) for estimation using distance-based methods in 2D local polynomial RD designs.
 Supported methods: [print.rd2d.dist](#), [summary.rd2d.dist](#).

print.rdbw2d	<i>Print Method for Bandwidth Selection for 2D Local Polynomial RD Design</i>
--------------	---

Description

The print method for bandwidth selection for 2D local polynomial RD design

Usage

```
## S3 method for class 'rdbw2d'
print(x, ...)
```

Arguments

`x` Class `rdbw2d` objects, obtained by calling `rdbw2d`.
`...` Additional arguments passed to the method (currently ignored).

Value

No return value, called to print `rdbw2d` results.

Author(s)

Matias D. Cattaneo, Princeton University. <cattaneo@princeton.edu>
 Rocío Titiunik, Princeton University. <titiunik@princeton.edu>
 Ruiqi Rae Yu, Princeton University. <rae.yu@princeton.edu>

See Also

`rdbw2d` for bandwidth selection for 2D local polynomial RD design
 Supported methods: `print.rdbw2d`, `summary.rdbw2d`.

<code>print.rdbw2d.dist</code>	<i>Print Method for Bandwidth Selection (Distance-Based) in 2D Local Polynomial RD Design</i>
--------------------------------	---

Description

Print method for displaying summary information from distance-based bandwidth selection in 2D local polynomial regression discontinuity (RD) designs, as produced by `rdbw2d.dist`.

Usage

```
## S3 method for class 'rdbw2d.dist'
print(x, ...)
```

Arguments

`x` An object of class `rdbw2d.dist`, returned by `rdbw2d.dist`.
`...` Additional arguments passed to the method (currently ignored).

Value

No return value. This function is called for its side effects: it prints summary information of `rdbw2d.dist`.

Author(s)

Matias D. Cattaneo, Princeton University. <cattaneo@princeton.edu>
 Rocío Titiunik, Princeton University. <titiunik@princeton.edu>
 Ruiqi Rae Yu, Princeton University. <rae.yu@princeton.edu>

See Also

`rdbw2d.dist` for distance-based bandwidth selection in 2D local polynomial RD design.

Supported methods: `print.rdbw2d.dist`, `summary.rdbw2d.dist`.

rd2d

Two-Dimensional Local Polynomial Regression Discontinuity Design

Description

`rd2d` implements bivariate local polynomial boundary regression discontinuity (RD) point estimators with robust bias-corrected pointwise confidence intervals and uniform confidence bands, developed in Cattaneo, Titiunik and Yu (2025a) with a companion software article Cattaneo, Titiunik and Yu (2025b). For robust bias-correction, see Calonico, Cattaneo, Titiunik (2014).

Companion commands are: `rdbw2d` for data-driven bandwidth selection.

For other packages of RD designs, visit <https://rdpackages.github.io/>

Usage

```
rd2d(
  Y,
  X,
  t,
  b,
  h = NULL,
  deriv = c(0, 0),
  tangvec = NULL,
  p = 1,
  q = 2,
  kernel = c("tri", "triangular", "epa", "epanechnikov", "uni", "uniform", "gau",
    "gaussian"),
  kernel_type = c("prod", "rad"),
  vce = c("hc1", "hc0", "hc2", "hc3"),
  masspoints = c("check", "adjust", "off"),
  C = NULL,
  level = 95,
  cbands = TRUE,
  side = c("two", "left", "right"),
  repp = 1000,
  bwselect = c("mserd", "imserd", "msetwo", "imsetwo", "user provided"),
  method = c("dpi", "rot"),
  bwcheck = 50 + p + 1,
  scaleregul = 3,
  scalebiasrcrt = 1,
  stdvars = TRUE
)
```

Arguments

Y	Dependent variable; a numeric vector of length N , where N is the sample size.
X	Bivariate running variable (a.k.a score variable); a numeric matrix or data frame of dimension $N \times 2$, with each row $\mathbf{X}_i = (X_{1i}, X_{2i})$.
t	Treatment indicator; a logical or binary vector indicating treatment assignment ($t_i = 1$ if treated, $t_i = 0$ otherwise).
b	Evaluation points; a matrix or data frame specifying boundary points $\mathbf{b}_j = (b_{1j}, b_{2j})$, of dimension $J \times 2$.
h	Bandwidths. Either a positive scalar (same bandwidth for all dimensions and groups), or a matrix/data frame of size $J \times 4$, corresponding to $h_{\text{control},1}$, $h_{\text{control},2}$, $h_{\text{treated},1}$, $h_{\text{treated},2}$ at each evaluation point. If not specified, bandwidth h is computed by the companion command <code>rdbw2d</code> . Default is $h = \text{NULL}$.
deriv	The order of the derivatives of the regression functions to be estimated; a numeric vector of length 2 specifying the number of derivatives in each coordinate (e.g., $c(1, 2)$ corresponds to $\partial_1 \partial_2^2$).
tangvec	Tangent vectors; a matrix or data frame of dimension $J \times 2$ specifying directional derivatives. Overrides <code>deriv</code> if provided.
p	Polynomial order for point estimation ($p = 1$ by default).
q	Polynomial order for robust confidence interval construction. Must satisfy $q \geq p$; default is $q = p + 1$.
kernel	Kernel function to use. Options are "unif", "uniform" (uniform), "triag", "triangular" (triangular, default), and "epan", "epanechnikov" (Epanechnikov).
kernel_type	Kernel structure. Either "prod" for product kernels (default) or "rad" for radial kernels.
vce	Variance-covariance estimation method. Options are: • "hc0": heteroskedasticity-robust plug-in residual variance estimator without small-sample adjustment. • "hc1": heteroskedasticity-robust plug-in residual variance estimator with HC1 small-sample adjustment (default). • "hc2": heteroskedasticity-robust plug-in residual variance estimator with HC2 adjustment. • "hc3": heteroskedasticity-robust plug-in residual variance estimator with HC3 adjustment.
masspoints	Handling of mass points in the running variable. Options are: • "check": detects presence of mass points and reports the number of unique observations (default). • "adjust": adjusts preliminary bandwidths to ensure a minimum number of unique observations within each side of the cutoff. • "off": ignores presence of mass points.
C	Cluster ID variable used for cluster-robust variance estimation. Default is $C = \text{NULL}$.

level	Nominal confidence level for intervals/bands, between 0 and 100 (default is 95).
cbands	Logical. If TRUE, also compute uniform confidence bands (default is FALSE).
side	Type of confidence interval. Options: "two" (two-sided, default), "left" (left tail), or "right" (right tail).
repp	Number of repetitions for critical value simulation (used in uniform confidence bands). Default is 1000.
bwselect	Bandwidth selection strategy. Options: • "mserd". One common MSE-optimal bandwidth selector for the boundary RD treatment effect estimator for each evaluation point (default). • "imserd". IMSE-optimal bandwidth selector for the boundary RD treatment effect estimator based on all evaluation points. • "msetwo". Two different MSE-optimal bandwidth selectors (control and treatment) for the boundary RD treatment effect estimator for each evaluation point. • "imsetwo". Two IMSE-optimal bandwidth selectors (control and treatment) for the boundary RD treatment effect estimator based on all evaluation points. • "user provided". User-provided bandwidths. If h is not NULL, then bwselect is overwritten to "user provided".
method	Bandwidth selection method for bias estimator based on local polynomials. Either "dpi" (default) for data-driven plug-in MSE optimal bandwidth selector or "rot" for rule-of-thumb bandwidth selector.
bwcheck	If a positive integer is provided, the preliminary bandwidth used in the calculations is enlarged so that at least bwcheck observations are used. If masspoints == "adjust", ensure at least bwcheck unique observations are used. The program stops with "not enough observations" if sample size $N < \text{bwcheck}$. Default is $50 + p + 1$.
scaleregul	Scaling factor for the regularization term in bandwidth selection. Default is 3.
scalebiasrcrt	Scaling factor used for bias correction based on higher order expansions. Default is 1.
stdvars	Logical. If TRUE, the running variables X_{1i} and X_{2i} are standardized before computing the bandwidths. Default is TRUE. Standardization only affects automatic bandwidth selection if bandwidths are not manually provided via h.

Value

An object of class "rd2d", a list with components:

results A data frame with point estimates, variances, p-values, confidence intervals, confidence bands, bandwidths and effective sample size at each evaluation point.

b1, b2 First and second coordinate of evaluation points $\mathbf{b} = (b_1, b_2)$.

Est.p Point estimate of $\hat{\tau}_p(\mathbf{b})$.

Se.p Standard error of $\hat{\tau}_p(\mathbf{b})$.

Est.q Bias-corrected point estimate of $\hat{\tau}_q(\mathbf{b})$.

`se.q` Standard error of bias-corrected estimate $\hat{\tau}_q(\mathbf{b})$.
`p-value` P-value based on t-statistic with bias-corrected estimate.
`CI.lower`, `CI.upper` Pointwise confidence intervals.
`CB.lower`, `CB.upper` Uniform confidence bands if computed.
`h01`, `h02`, `h11`, `h12` Bandwidths used in each coordinate and group. The four columns correspond to $h_{\text{control},1}$, $h_{\text{control},2}$, $h_{\text{treated},1}$, $h_{\text{treated},2}$ respectively.
`Nh0`, `Nh1` Effective sample size on each side of the cutoff.
`results.A0` Same structure as `results` but for control group outcomes.
`results.A1` Same structure as `results` but for treated group outcomes.
`cov.q` Covariance matrix for bias-corrected estimates $\hat{\tau}_q(\mathbf{b})$ for all point evaluations $\mathbf{b}$.
`opt` List of options used in the function call.
`rdmodel` String label for the RD model.

Author(s)

Matias D. Cattaneo, Princeton University. <cattaneo@princeton.edu>
 Rocío Titiunik, Princeton University. <titiunik@princeton.edu>
 Ruiqi Rae Yu, Princeton University. <rae.yu@princeton.edu>

References

- Cattaneo, M. D., Titiunik, R., Yu, R. R. (2025a). Estimation and Inference in Boundary Discontinuity Designs
- Cattaneo, M. D., Titiunik, R., Yu, R. R. (2025b). rd2d: Causal Inference in Boundary Discontinuity Designs
- Calonico, S., Cattaneo, M. D., Titiunik, R. (2014) Robust Nonparametric Confidence Intervals for Regression-Discontinuity Designs

See Also

[rdbw2d](#), [print.rd2d](#), [summary.rd2d](#)

Examples

```

# Simulated example
set.seed(123)
n <- 5000
X1 <- rnorm(n)
X2 <- rnorm(n)
t <- as.numeric(X1 > 0)
Y <- 3 + 2 * X1 + 1.5 * X2 + t + rnorm(n)
X <- cbind(X1, X2)
b <- matrix(c(0, 0, 0, 1), ncol = 2)

# Estimate treatment effect using rd2d
result <- rd2d(Y, X, t, b, cbands = TRUE)
print(result)
summary(result)

```

rd2d.dist

*Local Polynomial RD Estimation on Distance-Based Running Variables***Description**

rd2d.dist implements distance-based local polynomial boundary regression discontinuity (RD) point estimators with robust bias-corrected pointwise confidence intervals and uniform confidence bands, developed in Cattaneo, Titiunik and Yu (2025a) with a companion software article Cattaneo, Titiunik and Yu (2025b). For robust bias-correction, see Calonico, Cattaneo, Titiunik (2014).

Companion commands are: rdbw2d.dist for data-driven bandwidth selection.

For other packages of RD designs, visit <https://rdpackages.github.io/>

Usage

```
rd2d.dist(
  Y,
  D,
  h = NULL,
  b = NULL,
  p = 1,
  q = 2,
  kink = c("off", "on"),
  kernel = c("tri", "triangular", "epa", "epanechnikov", "uni", "uniform", "gau",
    "gaussian"),
  level = 95,
  cbands = TRUE,
  side = c("two", "left", "right"),
  repp = 1000,
  bwselect = c("mserd", "imserd", "msetwo", "imsetwo", "user provided"),
  vce = c("hc1", "hc0", "hc2", "hc3"),
  rbc = c("on", "off"),
  bwcheck = 50 + p + 1,
  masspoints = c("check", "adjust", "off"),
  C = NULL,
  scaleregul = 1,
  cqt = 0.5
)
```

Arguments

Y	Dependent variable; a numeric vector of length N , where N is the sample size.
D	Distance-based scores $\mathbf{D}_i = (\mathbf{D}_i(\mathbf{b}_1), \dots, \mathbf{D}_i(\mathbf{b}_J))$; dimension is $N \times J$ where N = sample size and J = number of cutoffs; non-negative values means data point in treatment group and negative values means data point in control group.

h	Bandwidth(s); if $c = h$ then same bandwidth is used for both groups; if a matrix of size $J \times 2$ is provided, each row contains $(h_{\text{control}}, h_{\text{tr}})$ for the evaluation point; if not specified, bandwidths are selected via <code>rdbw2d.dist()</code> .
b	Optional evaluation points; a matrix or data frame specifying boundary points $\mathbf{b}_j = (b_{1j}, b_{2j})$, dimension $J \times 2$.
p	Polynomial order for point estimation. Default is $p = 1$.
q	Polynomial order for bias-corrected estimation. Must satisfy $q \geq p$. Default is $q = p + 1$.
kink	Logical; whether to apply kink adjustment. Options: "on" or "off" (default).
kernel	Kernel function to use. Options are "unif", "uniform" (uniform), "triag", "triangular" (triangular, default), and "epan", "epanechnikov" (Epanechnikov).
level	Nominal confidence level for intervals/bands, between 0 and 100 (default is 95).
cbands	Logical. If TRUE, also compute uniform confidence bands (default is FALSE).
side	Type of confidence interval. Options: "two" (two-sided, default), "left" (left tail), or "right" (right tail).
repp	Number of bootstrap repetitions used for critical value simulation. Default is 1000.
bwselect	Bandwidth selection strategy. Options: • "mserd". One common MSE-optimal bandwidth selector for the boundary RD treatment effect estimator for each evaluation point (default). • "imserd". IMSE-optimal bandwidth selector for the boundary RD treatment effect estimator based on all evaluation points. • "msetwo". Two different MSE-optimal bandwidth selectors (control and treatment) for the boundary RD treatment effect estimator for each evaluation point. • "imsetwo". Two IMSE-optimal bandwidth selectors (control and treatment) for the boundary RD treatment effect estimator based on all evaluation points. • "user provided". User-provided bandwidths. If h is not NULL, then bwselect is overwritten to "user provided".
vce	Variance-covariance estimator for standard errors. Options: "hc0" Heteroskedasticity-robust variance estimator without small sample adjustment (White robust). "hc1" Heteroskedasticity-robust variance estimator with degrees-of-freedom correction (default). "hc2" Heteroskedasticity-robust variance estimator using leverage adjustments. "hc3" More conservative heteroskedasticity-robust variance estimator (similar to jackknife correction).
rbc	Logical. Whether to apply robust bias correction. Options: "on" (default) or "off". When kink = off, turn on rbc means setting q to p + 1. When kink = on, turn on rbc means shrinking the bandwidth selector to be proportional to $N^{-1/3}$.

bwcheck	If a positive integer is provided, the preliminary bandwidth used in the calculations is enlarged so that at least bwcheck observations are used. The program stops with “not enough observations” if sample size $N < \text{bwcheck}$. Default is $50 + p + 1$.
masspoints	Strategy for handling mass points in the running variable. Options: “check” Check for repeated values and adjust inference if needed (default). “adjust” Adjust bandwidths to guarantee a sufficient number of unique support points. “off” Ignore mass points completely.
C	Cluster ID variable used for cluster-robust variance estimation. Default is C = NULL.
scaleregul	Scaling factor for the regularization term in bandwidth selection. Default is 1.
cqt	Constant controlling subsample fraction for initial bias estimation. Default is 0.5.

Details

MSE bandwidth selection for geometrical RD design

Value

An object of class “rd2d.dist”, a list containing:

results A data frame with point estimates, variances, p-values, confidence intervals, confidence bands, and bandwidths at each evaluation point.

b1 First coordinate of the evaluation point.

b2 Second coordinate of the evaluation point.

Est.p Point estimate of $\hat{\tau}_{\text{dist},p}(\mathbf{b})$ with polynomial order p .

Se.p Standard error of $\hat{\tau}_{\text{dist},p}(\mathbf{b})$.

Est.q Bias-corrected estimate $\hat{\tau}_{\text{dist},q}(\mathbf{b})$ with polynomial order q .

Se.q Standard error of $\hat{\tau}_{\text{dist},q}(\mathbf{b})$.

pvalue Two-sided p-value based on $T_{\text{dist},q}(\mathbf{b})$.

CI.lower Lower bound of confidence interval.

CI.upper Upper bound of confidence interval.

CB.lower Lower bound of uniform confidence band (if cbands=TRUE).

CB.upper Upper bound of uniform confidence band (if cbands=TRUE).

h0 Bandwidth used for control group ($D_i(\mathbf{b}) < 0$).

h1 Bandwidth used for treatment group ($D_i(\mathbf{b}) \geq 0$).

Nh0 Effective sample size for control group.

Nh1 Effective sample size for treatment group.

results.A0 Same structure as **results** but for control group outcomes.

results.A1 Same structure as **results** but for treatment group outcomes.

tau.hat Vector of point estimates $\hat{\tau}_p(\mathbf{b})$.

se.hat Standard errors corresponding to $\hat{\tau}_p(\mathbf{b})$.

cb Confidence intervals and uniform bands.
 cov.q Covariance matrix for bias-corrected estimates $\hat{\tau}_{\text{dist},q}(\mathbf{b})$ for all point evaluations $\mathbf{b}$.
 opt List of options used in the function call.

Author(s)

Matias D. Cattaneo, Princeton University. <cattaneo@princeton.edu>
 Rocío Titiunik, Princeton University. <titiunik@princeton.edu>
 Ruiqi Rae Yu, Princeton University. <rae.yu@princeton.edu>

References

- Cattaneo, M. D., Titiunik, R., Yu, R. R. (2025a). Estimation and Inference in Boundary Discontinuity Designs
- Cattaneo, M. D., Titiunik, R., Yu, R. R. (2025b). rd2d: Causal Inference in Boundary Discontinuity Designs
- Calonico, S., Cattaneo, M. D., Titiunik, R. (2014) Robust Nonparametric Confidence Intervals for Regression-Discontinuity Designs

See Also

[rdbw2d.dist](#), [rd2d](#), [print.rd2d.dist](#), [summary.rd2d.dist](#)

Examples

```
set.seed(123)
n <- 5000

# Generate running variables x1 and x2
x1 <- rnorm(n)
x2 <- rnorm(n)

# Define treatment assignment: treated if x1 >= 0
d <- as.numeric(x1 >= 0)

# Generate outcome variable y with some treatment effect
y <- 3 + 2 * x1 + 1.5 * x2 + 1.5 * d + rnorm(n, sd = 0.5)

# Define evaluation points (e.g., at the origin and another point)
eval <- data.frame(x.1 = c(0, 0), x.2 = c(0, 1))

# Compute Euclidean distances to evaluation points
dist.a <- sqrt((x1 - eval$x.1[1])^2 + (x2 - eval$x.2[1])^2)
dist.b <- sqrt((x1 - eval$x.1[2])^2 + (x2 - eval$x.2[2])^2)

# Combine distances into a matrix
D <- as.data.frame(cbind(dist.a, dist.b))

# Assign positive distances for treatment group, negative for control
d_expanded <- matrix(rep(2 * d - 1, times = ncol(D)), nrow = nrow(D), ncol = ncol(D))
```

```

D <- D * d_expanded

# Run the rd2d.dist function
result <- rd2d.dist(y, D, b = eval)

# View the estimation results
print(result)
summary(result)

```

rdbw2d

Bandwidth Selection for 2D Local Polynomial RD Design

Description

rdbw2d implements bandwidth selector for bivariate local polynomial boundary regression discontinuity (RD) point estimators with robust bias-corrected pointwise confidence intervals and uniform confidence bands, developed in Cattaneo, Titiunik and Yu (2025a) with a companion software article Cattaneo, Titiunik and Yu (2025b). For robust bias-correction, see Calonico, Cattaneo, Titiunik (2014).

Companion commands are: rd2d for point estimation and inference procedures.

For other packages of RD designs, visit <https://rdpackages.github.io/>

Usage

```

rdbw2d(
  Y,
  X,
  t,
  b,
  p = 1,
  deriv = c(0, 0),
  tangvec = NULL,
  kernel = c("tri", "triangular", "epa", "epanechnikov", "uni", "uniform", "gau",
    "gaussian"),
  kernel_type = c("prod", "rad"),
  bwselect = c("mserd", "imserd", "msetwo", "imsetwo"),
  method = c("dpi", "rot"),
  vce = c("hc1", "hc0", "hc2", "hc3"),
  bwcheck = 50 + p + 1,
  masspoints = c("check", "adjust", "off"),
  C = NULL,
  scaleregul = 1,
  scalebiasrcrt = 1,
  stdvars = TRUE
)

```

Arguments

Y	Dependent variable; a numeric vector of length N , where N is the sample size.
X	Bivariate running variable (a.k.a score variable); a numeric matrix or data frame of dimension $N \times 2$, with each row $\mathbf{X}_i = (X_{1i}, X_{2i})$.
t	Treatment indicator; a logical or binary vector indicating treatment assignment ($t_i = 1$ if treated, $t_i = 0$ otherwise).
b	Evaluation points; a matrix or data frame specifying boundary points $\mathbf{b}_j = (b_{1j}, b_{2j})$, of dimension $J \times 2$.
p	Polynomial order of local polynomial estimator.
deriv	The order of the derivatives of the regression functions to be estimated; a numeric vector of length 2 specifying the number of derivatives in each coordinate (e.g., $c(1, 2)$ corresponds to $\partial_1 \partial_2^2$).
tangvec	Tangent vectors; a matrix or data frame of dimension $J \times 2$ specifying directional derivatives. Overrides deriv if provided.
kernel	Kernel function to use. Options are "unif", "uniform" (uniform), "triag", "triangular" (triangular, default), and "epan", "epanechnikov" (Epanechnikov).
kernel_type	Kernel structure. Either "prod" for product kernels (default) or "rad" for radial kernels.
bwselect	Bandwidth selection strategy. Options: • "mserd". One common MSE-optimal bandwidth selector for the boundary RD treatment effect estimator for each evaluation point (default). • "imserd". IMSE-optimal bandwidth selector for the boundary RD treatment effect estimator based on all evaluation points. • "msetwo". Two different MSE-optimal bandwidth selectors (control and treatment) for the boundary RD treatment effect estimator for each evaluation point. • "imsetwo". Two IMSE-optimal bandwidth selectors (control and treatment) for the boundary RD treatment effect estimator based on all evaluation points. • "user provided". User-provided bandwidths. If h is not NULL, then bwselect is overwritten to "user provided".
method	Bandwidth selection method for bias estimator based on local polynomials. Either "dpi" (default) for data-driven plug-in MSE optimal bandwidth selector or "rot" for rule-of-thumb bandwidth selector.
vce	Variance-covariance estimation method. Options are: • "hc0": heteroskedasticity-robust plug-in residual variance estimator without small-sample adjustment. • "hc1": heteroskedasticity-robust plug-in residual variance estimator with HC1 small-sample adjustment (default). • "hc2": heteroskedasticity-robust plug-in residual variance estimator with HC2 adjustment.

	• "hc3": heteroskedasticity-robust plug-in residual variance estimator with HC3 adjustment.
bwcheck	If a positive integer is provided, the preliminary bandwidth used in the calculations is enlarged so that at least bwcheck observations are used. If masspoints == "adjust", ensure at least bwcheck unique observations are used. The program stops with "not enough observations" if sample size $N < \text{bwcheck}$. Default is $50 + p + 1$.
masspoints	Handling of mass points in the running variable. Options are: • "check": detects presence of mass points and reports the number of unique observations (default). • "adjust": adjusts preliminary bandwidths to ensure a minimum number of unique observations within each side of the cutoff. • "off": ignores presence of mass points.
C	Cluster ID variable used for cluster-robust variance estimation. Default is C = NULL.
scaleregul	Scaling factor for the regularization term in bandwidth selection. Default is 3.
scalebiasrcrt	Scaling factor used for bias correction based on higher order expansions. Default is 1.
stdvars	Logical. If TRUE, the running variables X_{1i} and X_{2i} are standardized before computing the bandwidths. Default is TRUE. Standardization only affects automatic bandwidth selection if bandwidths are not manually provided via h.

Value

A list of class "rdbw2d" containing:

bws Data frame of estimated bandwidths for each evaluation point:

- b1 First coordinate of the evaluation point.
- b2 Second coordinate of the evaluation point.
- h01 Estimated bandwidth for X_{1i} in the control group ($\mathcal{A}_0$).
- h02 Estimated bandwidth for X_{2i} in the control group ($\mathcal{A}_0$).
- h11 Estimated bandwidth for X_{1i} in the treatment group ($\mathcal{A}_1$).
- h12 Estimated bandwidth for X_{2i} in the treatment group ($\mathcal{A}_1$).

mseconsts Data frame of intermediate quantities used in bandwidth calculation:

- Nh0 Effective sample size for the control group $\mathcal{A}_0$.
- Nh1 Effective sample size for the treatment group $\mathcal{A}_1$.
- bias.0 Bias constant estimate for the control group.
- bias.1 Bias constant estimate for the treatment group.
- var.0 Variance constant estimate for the control group.
- var.1 Variance constant estimate for the treatment group.
- reg.bias.0 Bias correction adjustment for the control group.
- reg.bias.1 Bias correction adjustment for the treatment group.
- reg.var.0 Variance of the bias estimate for the control group.

reg.var.1 Variance of the bias estimate for the treatment group.

opt List containing:

- p Polynomial order used for estimation.
- kernel Kernel function used.
- kernel_type Type of kernel (product or radial).
- stdvars Logical indicating if standardization was applied.
- bwselect Bandwidth selection strategy used.
- method Bandwidth estimation method.
- vce Variance estimation method.
- scaleregul Scaling factor for regularization.
- scalebiasrcrt Scaling factor for bias correction.
- N Total sample size N .

Author(s)

Matias D. Cattaneo, Princeton University. <cattaneo@princeton.edu>
 Rocío Titiunik, Princeton University. <titiunik@princeton.edu>
 Ruiqi Rae Yu, Princeton University. <rae.yu@princeton.edu>

References

- Cattaneo, M. D., Titiunik, R., Yu, R. R. (2025a). Estimation and Inference in Boundary Discontinuity Designs
- Cattaneo, M. D., Titiunik, R., Yu, R. R. (2025b). rd2d: Causal Inference in Boundary Discontinuity Designs
- Calonico, S., Cattaneo, M. D., Titiunik, R. (2014) Robust Nonparametric Confidence Intervals for Regression-Discontinuity Designs

See Also

[rd2d](#), [print.rdbw2d](#), [summary.rdbw2d](#)

Examples

```
# Simulated example
set.seed(123)
n <- 5000
X1 <- rnorm(n)
X2 <- rnorm(n)
t <- as.numeric(X1 > 0)
Y <- 3 + 2 * X1 + 1.5 * X2 + t + rnorm(n)
X <- cbind(X1, X2)
b <- matrix(c(0, 0, 0, 1), ncol = 2)

# MSE optimal bandwidth for rd2d
bws <- rdbw2d(Y, X, t, b)

# View the bandwidth selection results
```

```
print(bws)
summary(bws)
```

rdbw2d.dist

Bandwidth Selection for Distance-Based RD Designs

Description

rdbw2d.dist implements bandwidth selector for distance-based local polynomial boundary regression discontinuity (RD) point estimators with robust bias-corrected pointwise confidence intervals and uniform confidence bands, developed in Cattaneo, Titiunik and Yu (2025a) with a companion software article Cattaneo, Titiunik and Yu (2025b). For robust bias-correction, see Calonico, Cattaneo, Titiunik (2014).

Usage

```
rdbw2d.dist(
  Y,
  D,
  b = NULL,
  p = 1,
  kink = c("off", "on"),
  kernel = c("tri", "triangular", "epa", "epanechnikov", "uni", "uniform", "gau",
    "gaussian"),
  bwselect = c("mserd", "imserd", "msetwo", "imsetwo"),
  vce = c("hc1", "hc0", "hc2", "hc3"),
  bwcheck = 20 + p + 1,
  masspoints = c("check", "adjust", "off"),
  C = NULL,
  scaleregul = 1,
  cqt = 0.5
)
```

Arguments

Y	Dependent variable; a numeric vector of length N , where N is the sample size.
D	Distance-based scores $\mathbf{D}_i = (\mathbf{D}_i(\mathbf{b}_1), \dots, \mathbf{D}_i(\mathbf{b}_J))$; dimension is $N \times J$ where N = sample size and J = number of cutoffs; non-negative values means data point in treatment group and negative values means data point in control group.
b	Optional evaluation points; a matrix or data frame specifying boundary points $\mathbf{b}_j = (b_{1j}, b_{2j})$, dimension $J \times 2$.
p	Polynomial order for point estimation. Default is $p = 1$.
kink	Logical; whether to apply kink adjustment. Options: "on" or "off" (default).
kernel	Kernel function to use. Options are "unif", "uniform" (uniform), "triag", "triangular" (triangular, default), and "epa", "epanechnikov" (Epanechnikov).

bwselect	Bandwidth selection strategy. Options: • "mserd". One common MSE-optimal bandwidth selector for the boundary RD treatment effect estimator for each evaluation point (default). • "imserd". IMSE-optimal bandwidth selector for the boundary RD treatment effect estimator based on all evaluation points. • "msetwo". Two different MSE-optimal bandwidth selectors (control and treatment) for the boundary RD treatment effect estimator for each evaluation point. • "imsetwo". Two IMSE-optimal bandwidth selectors (control and treatment) for the boundary RD treatment effect estimator based on all evaluation points. • "user provided". User-provided bandwidths. If <code>h</code> is not NULL, then <code>bwselect</code> is overwritten to "user provided".
vce	Variance-covariance estimator for standard errors. Options: "hc0" Heteroskedasticity-robust variance estimator without small sample adjustment (White robust). "hc1" Heteroskedasticity-robust variance estimator with degrees-of-freedom correction (default). "hc2" Heteroskedasticity-robust variance estimator using leverage adjustments. "hc3" More conservative heteroskedasticity-robust variance estimator (similar to jackknife correction).
bwcheck	If a positive integer is provided, the preliminary bandwidth used in the calculations is enlarged so that at least <code>bwcheck</code> observations are used. The program stops with "not enough observations" if sample size $N < \text{bwcheck}$. Default is $50 + p + 1$.
masspoints	Strategy for handling mass points in the running variable. Options: "check" Check for repeated values and adjust inference if needed (default). "adjust" Adjust bandwidths to guarantee a sufficient number of unique support points. "off" Ignore mass points completely.
C	Cluster ID variable used for cluster-robust variance estimation with degrees-of-freedom weights. Default is <code>C = NULL</code>.
scaleregul	Scaling factor for the regularization term in bandwidth selection. Default is 1.
cqt	Constant controlling subsample fraction for initial bias estimation. Default is 0.5.

Value

An object of class "rdbw2d.dist", containing:

`bws` Data frame of optimal bandwidths for each evaluation point:

- `b1` First coordinate of the evaluation point $b1$.
- `b2` Second coordinate of the evaluation point $b2$.
- `h0` Bandwidth for observations with distance $D_i(\mathbf{b}) < 0$.

h1 Bandwidth for observations with distance $D_i(\mathbf{b}) \geq 0$.
 Nh0 Effective sample size for $D_i(\mathbf{b}) < 0$.
 Nh1 Effective sample size for $D_i(\mathbf{b}) \geq 0$.
 mseconsts Data frame of intermediate bias and variance constants used for MSE/IMSE calculations.
 opt List of options used in the function call.

Author(s)

Matias D. Cattaneo, Princeton University. <cattaneo@princeton.edu>
 Rocío Titiunik, Princeton University. <titiunik@princeton.edu>
 Ruiqi Rae Yu, Princeton University. <rae.yu@princeton.edu>

References

- Cattaneo, M. D., Titiunik, R., Yu, R. R. (2025a). Estimation and Inference in Boundary Discontinuity Designs
- Cattaneo, M. D., Titiunik, R., Yu, R. R. (2025b). rd2d: Causal Inference in Boundary Discontinuity Designs
- Calonico, S., Cattaneo, M. D., Titiunik, R. (2014) Robust Nonparametric Confidence Intervals for Regression-Discontinuity Designs

See Also

[rd2d.dist](#), [rd2d](#), [summary.rdbw2d.dist](#), [print.rdbw2d.dist](#)

Examples

```
set.seed(123)
n <- 5000

# Generate running variables x1 and x2
x1 <- rnorm(n)
x2 <- rnorm(n)

# Define treatment assignment: treated if x1 >= 0
d <- as.numeric(x1 >= 0)

# Generate outcome variable y with some treatment effect
y <- 3 + 2 * x1 + 1.5 * x2 + 1.5 * d + rnorm(n, sd = 0.5)

# Define evaluation points (e.g., at the origin and another point)
eval <- data.frame(x.1 = c(0, 0), x.2 = c(0, 1))

# Compute Euclidean distances to evaluation points
dist.a <- sqrt((x1 - eval$x.1[1])^2 + (x2 - eval$x.2[1])^2)
dist.b <- sqrt((x1 - eval$x.1[2])^2 + (x2 - eval$x.2[2])^2)

# Combine distances into a matrix
D <- as.data.frame(cbind(dist.a, dist.b))
```

```

# Assign positive distances for treatment group, negative for control
d_expanded <- matrix(rep(2 * d - 1, times = ncol(D)), nrow = nrow(D), ncol = ncol(D))
D <- D * d_expanded

# Run the rd2d.dist function
bws <- rdbw2d.dist(y, D, b = eval)

# View the estimation results
print(bws)
summary(bws)

```

summary.rd2d

*Summary Method for 2D Local Polynomial RD Estimation***Description**

Summarizes estimation and bandwidth results from a 2D local polynomial regression discontinuity (RD) design, as produced by [rd2d](#).

Usage

```

## S3 method for class 'rd2d'
summary(object, ...)

```

Arguments

object	An object of class rd2d, typically returned by rd2d .
...	Optional arguments. Supported options include: • CBuniform: Logical. If TRUE, displays uniform confidence bands; if FALSE (default), displays pointwise confidence intervals. • subset: Integer vector of indices of evaluation points to display. Defaults to all evaluation points. • output: Character. Use "main" to display estimation results, or "bw" to display bandwidth information. Default is "main". • sep_main: Integer vector of controlling the column widths of the output table when output = "main". Default is c(4, 7, 7, 7, 7, 7, 17). • sep_bw: Integer vector of controlling the column widths of the output table when output = "bw". Default is c(4, rep(8, 8)). • WBATE: Integer vector of weights for aggregated average treatment effect (WBATE). Should have non-negative entries summing up to one. If provided, an extra row for WBATE is added to the output table. • LBATE: Logical. If TRUE, an extra row for largest treatment effect (LBATE) is added to the output table.

Value

No return value. This function is called for its side effects: it prints a formatted summary of `rd2d` results.

Author(s)

Matias D. Cattaneo, Princeton University. <cattaneo@princeton.edu>
 Rocío Titiunik, Princeton University. <titiunik@princeton.edu>
 Ruiqi Rae Yu, Princeton University. <rae.yu@princeton.edu>

See Also

`rd2d` for estimation using 2D local polynomial RD design.

Supported methods: `print.rd2d`, `summary.rd2d`.

summary.rd2d.dist	<i>Summary Method for 2D Local Polynomial RD Estimation (Distance-Based)</i>
-------------------	--

Description

Summarizes estimation and bandwidth results from a 2D local polynomial regression discontinuity (RD) design using distance-based methods, as returned by `rd2d.dist`.

Usage

```
## S3 method for class 'rd2d.dist'
summary(object, ...)
```

Arguments

object	An object of class <code>rd2d.dist</code> , returned by <code>rd2d.dist</code> .
...	Optional arguments. Supported options include: • <code>CBuniform</code>: Logical. If <code>TRUE</code>, displays uniform confidence bands; if <code>FALSE</code> (default), displays pointwise confidence intervals. • <code>subset</code>: Integer vector of indices of evaluation points to display. Defaults to all evaluation points. • <code>output</code>: Character. Use <code>"main"</code> to display estimation results, or <code>"bw"</code> to display bandwidth information. Default is <code>"main"</code>. • <code>sep_main</code>: Integer vector of length seven controlling the column widths of the output table when <code>output = "main"</code>. Default is <code>c(4, 7, 7, 7, 7, 7, 17)</code>. When <code>b</code> is not provided, output table has five columns, the second and third entry of <code>sep_main</code> are not used, and can be any place holder.

- `sep_bw`: Integer vector of length seven controlling the column widths of the output table when `output = "bw"`. Default is `c(4, rep(8, 6))`. When `b` is not provided, output table has five columns, the second and third entry of `sep_bw` are not used, and can be any place holder.
- `WBATE`: Integer vector of weights for aggregated average treatment effect (WBATE). Should have non-negative entries summing up to one. If provided, an extra row for WBATE is added to the output table.
- `LTE`: Logical. If `TRUE`, an extra row for largest treatment effect (LTE) is added to the output table.

Value

No return value. This function is called for its side effects: it prints a formatted summary of `rd2d.dist` results.

Author(s)

Matias D. Cattaneo, Princeton University. <cattaneo@princeton.edu>
 Rocío Titiunik, Princeton University. <titiunik@princeton.edu>
 Ruiqi Rae Yu, Princeton University. <rae.yu@princeton.edu>

See Also

`rd2d.dist` for estimation using distance-based 2D local polynomial RD design.
 Supported methods: `print.rd2d.dist`, `summary.rd2d.dist`.

<code>summary.rdbw2d</code>	<i>Summary Method for Bandwidth Selection for 2D Local Polynomial RD Design</i>
-----------------------------	---

Description

Summary method for objects of class `rdbw2d`, displaying bandwidth selection results for 2D local polynomial regression discontinuity designs.

Usage

```
## S3 method for class 'rdbw2d'
summary(object, ...)
```

Arguments

<code>object</code>	An object of class <code>rdbw2d</code> , typically returned by <code>rdbw2d</code> .
<code>...</code>	Optional arguments. Supported options include: • <code>subset</code>: Integer vector of indices of evaluation points to display. Defaults to all evaluation points. • <code>sep</code>: Integer vector of controlling the column widths of the output table. Default is <code>c(4, rep(8, 6))</code>.

Value

No return value. Called for its side effects of printing a formatted summary of `rdbw2d` results.

Author(s)

Matias D. Cattaneo, Princeton University. <cattaneo@princeton.edu>
 Rocío Titiunik, Princeton University. <titiunik@princeton.edu>
 Ruiqi Rae Yu, Princeton University. <rae.yu@princeton.edu>

See Also

`rdbw2d` for bandwidth selection in 2D local polynomial RD design.

Supported methods: `print.rdbw2d`, `summary.rdbw2d`.

summary.rdbw2d.dist	<i>Summary Method for Bandwidth Selection in 2D Local Polynomial RD Design (Distance-Based)</i>
---------------------	---

Description

Summarizes bandwidth selection results from a 2D local polynomial regression discontinuity (RD) design using distance-based methods, as returned by `rdbw2d.dist`.

Usage

```
## S3 method for class 'rdbw2d.dist'
summary(object, ...)
```

Arguments

object	An object of class <code>rdbw2d.dist</code> , returned by <code>rdbw2d.dist</code> .
...	Optional arguments. Supported options include: • <code>subset</code>: Integer vector of indices of evaluation points to display. Defaults to all evaluation points. • <code>sep</code>: Integer vector of length five controlling the column widths of the output table. Default is <code>c(4, 8, 8, 14, 14)</code>. When <code>b</code> is not provided, output table has three columns, the second and third entry of <code>sep</code> are not used, and can be any place holder.

Value

No return value. This function is called for its side effects: it prints a formatted summary of `rdbw2d.dist` results.

Author(s)

Matias D. Cattaneo, Princeton University. <cattaneo@princeton.edu>

Rocío Titiunik, Princeton University. <titiunik@princeton.edu>

Ruiqi Rae Yu, Princeton University. <rae.yu@princeton.edu>

See Also

[rdbw2d.dist](#) for bandwidth selection using 2D local polynomial RD design with distance-based methods.

Supported methods: [print.rdbw2d.dist](#), [summary.rdbw2d.dist](#).

Index

`print.rd2d`, [3](#), [3](#), [9](#), [22](#)
`print.rd2d.dist`, [4](#), [4](#), [13](#), [23](#)
`print.rdbw2d`, [4](#), [5](#), [17](#), [24](#)
`print.rdbw2d.dist`, [5](#), [6](#), [20](#), [25](#)

`rd2d`, [2](#), [3](#), [6](#), [13](#), [17](#), [20–22](#)
`rd2d-package`, [2](#)
`rd2d.dist`, [2](#), [4](#), [10](#), [20](#), [22](#), [23](#)
`rdbw2d`, [2](#), [5](#), [9](#), [14](#), [23](#), [24](#)
`rdbw2d.dist`, [2](#), [5](#), [6](#), [13](#), [18](#), [24](#), [25](#)

`summary.rd2d`, [3](#), [9](#), [21](#), [22](#)
`summary.rd2d.dist`, [4](#), [13](#), [22](#), [23](#)
`summary.rdbw2d`, [5](#), [17](#), [23](#), [24](#)
`summary.rdbw2d.dist`, [6](#), [20](#), [24](#), [25](#)